

Package ‘DataViz’

July 21, 2025

Type Package

Title Data Visualisation Using an HTML Page and 'D3.js'

Version 0.2.8

Date 2019-09-16

Maintainer Timothy Bell <horia.yeb@gmail.com>

Description Gives access to data visualisation methods that are relevant from the statistician's point of view. Using 'D3's existing data visualisation tools to empower R language and environment. The throw chart method is a line chart used to illustrate paired data sets (such as before-after, male-female).

License GPL (>= 2)

Imports Rcpp (>= 1.0.0)

LinkingTo Rcpp

Depends tibble

LazyData true

NeedsCompilation yes

Author Timothy Bell [aut, cre],
Christophe Genolini [aut, ths]

Repository CRAN

Date/Publication 2019-09-16 17:10:03 UTC

Contents

DataViz-package	2
forcelayout	3
oldestpeople	3
quad	4
rcpp_forcelayout	4
rcpp_throwchart	5
r_forcelayout	6
r_throwchart	6
throwchart	7
weekschedule	8
Workweek	8

DataViz-package ~ Overview: package DataViz ~

Description

Various data vizualisation methods.

Details

Data Visualisation is the art of graphically representing data. There are numerous data visualisation methods, but they aren't always relevant -and sometimes less informative than basic representations-. Moreover they are often created by programmers in various computer languages and the code being seldom available.

DataViz is a package aiming to give access to Data Visualisation methods that are relevant from the statistician's point of view.

The 3 first methods to be implemented are [throwchart](#), Gravity Bubble Chart (V0.3, june 2019) and XXX (V0.4, septembre 2019)

Author(s)

Timothy Bell <horia.yeb@gmail.com> Christophe Genolini <christophe.genolini@u-paris10.fr>

Maintainer: Timothy Bell <horia.yeb@gmail.com>

References

Inspired from <http://tiffanyfrance.com/data-is-beautiful/19-01/>

See Also

[throwchart forcelayout](#)

Examples

```
if(interactive()){
  throwchart(c(1,2),c(2,8),c("#000", "#F82"),id = c("id1","id2"),c(1,5))
  throwchart(c(1,2),c(2,8))
}
if(!interactive()){
  throwchart(c(1,2),c(2,8), offSet = 1, webinteract=FALSE)
  throwchart(c(1,2),c(2,1), webinteract=FALSE)
  throwchart(c(1,2),c(2,8),c("#000", "#F00"),c(1,5), webinteract=FALSE)
}
```

forcelayout *~ Main function: forcelayout ~*

Description

forcelayout method is a dynamic method showing longitudinal data set evolution.

Usage

```
forcelayout(schedule, webinteract, ttime)
```

Arguments

schedule [numeric] or [integer]: A (non-empty) vector of data values.
webinteract [bool]: Is the function used in interactive mode?
ttime [string]: A (non-empty) time-unit value to fetch data from data.frame.

Examples

```
if(interactive()){  
  forcelayout(weekschedule)  
}  
if(!interactive()){  
  forcelayout(weekschedule, webinteract = FALSE, ttime = "Monday")  
}
```

oldestpeople *~ List of the oldest people in the world data set ~*

Description

This is data from <http://www.grg.org/Adams/Deaths2012.HTM>, a list of all the oldest people in history holding the record.

quad ~ *Quadratic fitting function: quad* ~

Description

Fits a set of paired points with a quadratic curve. Returns the quadratic set of points. Function only called by `r_throwchart`.

Usage

```
quad(point,before_point,after_point,offSet)
```

Arguments

point	[numeric] or [integer]: A set of points between before and after points.
before_point	[numeric] or [integer]: The first point of the curve.
after_point	[numeric] or [integer]: The last point of the curve.
offSet	[integer]: Single value offset for the graph.

Value

returns the quadratic point equivalent.

rcpp_forcelayout ~ *C++ called function: rcpp_forcelayout* ~

Description

This function takes the inputs from [forcelayout](#), and writes the data in Json array, then this function calls a windows cmd function to open an index.html in the extdata.

Usage

```
rcpp_forcelayout(schedule, path)
```

Arguments

schedule	A number column
path	The path for the library

Examples

```
if(interactive()){
  rcpp_throwchart(weekschedule,path.package("DataViz"))
}
```

rcpp_throwchart ~ C++ called function: rcpp_throwchart ~

Description

This function takes the inputs from [throwchart](#), and writes the data in Json array, then this function calls a windows cmd function to open an index.html in the extdata.

Usage

```
rcpp_throwchart(before, after ,col, id, lwd, xlim, ylim, offSet, path)
```

Arguments

before	A number column
after	A number column
col	A hex code colour colum has to be format "#000"
id	An id has to be string
lwd	A number for the line width best between 1-5)
xlim	[numeric]: 2 value colum with x limits.
ylim	[numeric]: 2 value colum with y limits.
offSet	[integer]: Single value for the graph offset.
path	The path for the library

Examples

```
if(interactive()){  
  before = tibble(c(1,2))  
  after = tibble(c(2,8))  
  col = tibble(c("#000", "#F82"))  
  id = tibble(c("", ""))  
  lwd = tibble(c(1,5))  
  xlim = tibble(c(0,0))  
  rcpp_throwchart(before,after,col,id,lwd,xlim,0,path.package("DataViz"))}
```

r_forcelayout ~ R graphics function: r_forcelayout ~

Description

Used when interactive is false and creates a plot through R of this data visualisation method.

Usage

```
r_forcelayout(schedule, ttime)
```

Arguments

schedule [string]: A (non-empty) data.frame of data values.
 ttime [string]: A (non-empty) time-unit value to fetch data from data.frame.

Examples

```
if(interactive()){
  r_forcelayout(weekschedule,ttime = "Tuesday")
}
```

r_throwchart ~ R graphics function: r_throwchart ~

Description

Used when interactive is false and creates a plot through R of this data visualisation method.

Usage

```
r_throwchart(before, after,xlim, ylim, col, lwd, offSet)
```

Arguments

before [numeric] or [integer]: A (non-empty) vector of data values.
 after [numeric] or [integer]: A (non-empty) vector of data values.
 col [character]: A vector of hex code colours, by default "#123".
 lwd [integer]: Line width, a column of line widths, by default value is 2.5.
 xlim [numeric]: 2 value colum with x limits.
 ylim [numeric]: 2 value colum with y limits.
 offSet [integer]: Single value offset for the graph.

Examples

```
if(interactive()){
  r_throwchart(tibble(c(1,2)),tibble(c(2,8)),c(0,0),c(0,0),col = "blue", c(1,5), offSet = 1)
}
```

 throwchart

 ~ Main function: throwchart ~

Description

Throwchart method is useful for visualising paired data, such as before/after data sets. Each pair of points are set on a horizontal axis and joined by a parabola. The height of the parabola is proportional to the difference: after- before = difference. If the difference is negative (after < before) then the curve is drawn under the axis.

Usage

```
throwchart(before, after, col, id, lwd, xlim, ylim, offSet, webinteract)
```

Arguments

before	[numeric] or [integer]: A (non-empty) vector of data values.
after	[numeric] or [integer]: A (non-empty) vector of data values.
col	[character]: A vector of hex code colours, by default "#123".
id	[factor]: Column of string or number identifiers.
lwd	[integer]: Line width, a column of line widths, by default value is 2.5.
xlim	[numeric]: 2 value column with x limits.
ylim	[numeric]: 2 value column with y limits.
offSet	[integer]: Single value offset for the graph.
webinteract	[bool]: Is the function used in interactive mode?

Examples

```
if(interactive()){
  throwchart(c(1,2),c(2,8),c("#000","#F82"),id = c("id1","id2"),c(1,5))
  throwchart(c(1,2),c(2,8), offSet = 1, webinteract=TRUE)
}
if(!interactive()){
  throwchart(c(1,2),c(2,8), offSet = 1, webinteract=FALSE)
  throwchart(c(1,2),c(2,1), webinteract=FALSE)
  throwchart(c(1,2),c(2,8),c("#000","#F00"),id = c("id1","id2"),c(1,5), webinteract=FALSE)
}
n <- 10
Avant <- rnorm(n)
Apres <- Avant + rnorm(n) + 10
throwchart(Avant, Apres, xlim = c(-4,14), webinteract = FALSE)
throwchart(Avant, Apres, offSet = 0, webinteract = FALSE)
throwchart(Avant, Apres, offSet = 8, webinteract = FALSE)
}
```

weekschedule ~ *Example data set number 2 for force layout* ~

Description

Set for force layout, artificial data.

Workweek ~ *Example data set for force layout* ~

Description

Set for force layout, artificial data.

Index

* **DataViz**

DataViz-package, [2](#)

DataViz (DataViz-package), [2](#)

DataViz-package, [2](#)

forcelayout, [2](#), [3](#), [4](#)

oldestpeople, [3](#)

quad, [4](#)

r_forcelayout, [6](#)

r_throwchart, [6](#)

rcpp_forcelayout, [4](#)

rcpp_throwchart, [5](#)

throwchart, [2](#), [5](#), [7](#)

weekschedule, [8](#)

Workweek, [8](#)