

Package ‘contactsurveys’

May 8, 2026

Title Download Contact Surveys for Use in Infectious Disease Modelling

Version 0.1.0

Description Download, cache, and manage social contact survey data from the social contact data community on Zenodo (https://zenodo.org/communities/social_contact_data) for use in infectious disease modelling. Provides functions to list available surveys, download survey files with automatic caching, and retrieve citations. Contact survey data describe who contacts whom in a population and are used to parameterise age-structured transmission models, for example via the 'socialmixr' package. The surveys available include those from the POLYMOD study (Mossong et al. (2008) [doi:10.1371/journal.pmed.0050074](https://doi.org/10.1371/journal.pmed.0050074)) and other social contact data shared on Zenodo.

License MIT + file LICENSE

Language en-US

Depends R (>= 4.1.0)

Imports cli (>= 3.6.0), data.table, oai, purrr, rlang (>= 1.0.0), stats, yesno, zen4R (>= 0.10.3)

Suggests socialmixr (>= 0.5.0), knitr, rmarkdown, roxyglobals, testthat (>= 3.0.0), withr, vcr (>= 2.0.0)

VignetteBuilder knitr

Encoding UTF-8

NeedsCompilation no

RoxygenNote 7.3.3

URL <https://github.com/epiforecasts/contactsurveys>,
<http://epiforecasts.io/contactsurveys/>

BugReports <https://github.com/epiforecasts/contactsurveys/issues>

Config/testthat/edition 3

Config/roxyglobals/filename globals.R

Config/roxyglobals/unique FALSE

Author Sebastian Funk [aut, cre, cph] (ORCID: <https://orcid.org/0000-0002-2842-3406>),
 Nicholas Tierney [aut] (ORCID: <https://orcid.org/0000-0003-1460-8722>),
 Hugo Gruson [ctb] (ORCID: <https://orcid.org/0000-0002-4094-1476>)

Maintainer Sebastian Funk <sebastian.funk@lshtm.ac.uk>

Repository CRAN

Date/Publication 2026-01-31 19:20:02 UTC

Contents

contactsurveys_dir	2
delete_contactsurveys_files	3
delete_survey	4
download_survey	4
get_citation	5
is_doi	6
list_surveys	7
ls_contactsurveys	7
print.csbib	8

Index **9**

contactsurveys_dir *Directory for persistent storage of contact surveys*

Description

Returns a platform-specific directory for persistent storage of downloaded survey files, powered by [tools::R_user_dir\(\)](#). You can override this by setting the environment variable CONTACTSURVEYS_HOME.

Usage

```
contactsurveys_dir()
```

Details

By default, [download_survey\(\)](#) and [list_surveys\(\)](#) use [tempdir\(\)](#) so files do not persist across R sessions. To enable persistent caching, pass [contactsurveys_dir\(\)](#) as the directory argument, e.g. [download_survey\(survey, directory = contactsurveys_dir\(\)\)](#).

Value

the active contactsurveys directory.

Examples

```
contactsurveys_dir()

## Override with an environment variable:
Sys.setenv(CONTACTSURVEYS_HOME = tempdir())
contactsurveys_dir()
## Unset
Sys.unsetenv("CONTACTSURVEYS_HOME")
```

```
delete_contactsurveys_files
      Delete files in contactsurveys directory
```

Description

Delete files in contactsurveys directory

Usage

```
delete_contactsurveys_files(dir = contactsurveys_dir())
delete_contactsurveys_dir(dir = contactsurveys_dir())
```

Arguments

`dir` directory to list files to delete from

Value

nothing, deletes files.

Examples

```
delete_contactsurveys_files()
```

delete_survey *Delete files for a given survey*

Description

For when you want to delete files associated with a given survey.

Usage

```
delete_survey(survey)
```

Arguments

survey Survey, as used in [download_survey\(\)](#).

Value

nothing, deleted files

See Also

[delete_contactsurveys_dir\(\)](#) [delete_contactsurveys_files\(\)](#)

Examples

```
peru_doi <- "https://doi.org/10.5281/zenodo.1095664"  
delete_survey(peru_doi)
```

download_survey *Download a survey from its Zenodo repository*

Description

Downloads survey data. Uses a caching mechanism via the default argument for directory.

Usage

```
download_survey(  
  survey,  
  directory = tempdir(),  
  verbose = TRUE,  
  overwrite = FALSE,  
  timeout = 3600,  
  rate = purrr::rate_backoff(pause_base = 5, max_times = 4)  
)
```

Arguments

survey	A DOI of a survey, (see list_surveys()). If a HTML link is given, the DOI will be isolated and used.
directory	Directory of where to save survey files. Defaults to tempdir() , so files do not persist across R sessions. For persistent caching, pass contactsurveys_dir() , which uses tools::R_user_dir() and appends the survey URL/DOI base-name as a subdirectory. E.g., if you provide "10.5281/zenodo.1095664" in the survey argument, it will save the surveys into a directory zenodo.1095664 under contactsurveys_dir() . You can also set an environment variable, CONTACTSURVEYS_HOME, see Sys.setenv() or Renviron for more detail.
verbose	Whether downloads should be echoed to output. Default TRUE.
overwrite	If files should be overwritten if they already exist. Default FALSE
timeout	A numeric value specifying timeout in seconds. Default 3600 seconds.
rate	a purrr rate object, to facilitate downloading if the download fails. Defaults to an exponential backoff of 5 seconds (up to 4 attempts: 1 initial + 3 retries) changed by specifying your own rate object, see ?purrr::rate_backoff() for details.

Value

a vector of filenames, where the surveys were downloaded

See Also

[list_surveys\(\)](#)

Examples

```
list_surveys()
peru_survey <- download_survey("https://doi.org/10.5281/zenodo.1095664")
```

get_citation

Get citation from a DOI

Description

This is a wrapper around [zen4R::get_citation\(\)](#) with a couple of smaller changes. Firstly, it silences output from [zen4R::get_citation\(\)](#), secondly the default citation style is "apa".

Usage

```
get_citation(
  doi,
  style = c("bibtex", "apa", "harvard-cite-them-right", "modern-language-association",
            "vancouver", "chicago-fullnote-bibliography", "ieee"),
  verbose = TRUE
)
```

Arguments

doi	A string, the Zenodo DOI or concept DOI.
style	A string, the citation style. Default is "bibtex". Possible values are: "bibtex", "harvard-cite-them-right", "apa", "modern-language-association", "vancouver", "chicago-fullnote-bibliography", or "ieee".
verbose	logical. Should messages during citation fetching print to the screen? Default is TRUE.

Value

A character string containing the citation in the requested style. For "bibtex" style, returns an object of class "csbib".

Examples

```
polymod_doi <- "https://doi.org/10.5281/zenodo.3874557"
get_citation(polymod_doi)
```

is_doi	<i>Checks if a character string is a DOI</i>
--------	--

Description

Checks if a character string is a DOI

Usage

```
is_doi(x)
```

Arguments

x	Character vector; the string or strings to check
---	--

Value

Logical; TRUE if x is a DOI, FALSE otherwise

Author(s)

Sebastian Funk

list_surveys	<i>List all surveys available for download</i>
--------------	--

Description

List all surveys available for download

Usage

```
list_surveys(  
  directory = tempdir(),  
  overwrite = FALSE,  
  verbose = TRUE,  
  rate = purrr::rate_backoff(pause_base = 5, max_times = 4)  
)
```

Arguments

directory	Directory to save the cached survey list. Defaults to <code>tempdir()</code> , so the cached list does not persist across R sessions. For persistent caching, pass <code>contactsurveys_dir()</code> .
overwrite	If files should be overwritten if they already exist. Default FALSE
verbose	Whether downloads should be echoed to output. Default TRUE.
rate	a <code>purrr rate</code> object, to facilitate downloading if the download fails. Defaults to an exponential backoff of 5 seconds (up to 4 attempts: 1 initial + 3 retries) changed by specifying your own rate object, see <code>?purrr::rate_backoff()</code> for details.

Value

data.table with columns: date_added, title, creator, url

Examples

```
list_surveys()
```

ls_contactsurveys	<i>List files in contactsurveys cache</i>
-------------------	---

Description

It can be handy to see which files are available, sometimes to return to a clean slate and delete them via the `delete_contactsurveys_*` functions.

Usage

```
ls_contactsurveys(dir = contactsurveys_dir())
```

Arguments

dir Directory to list. Default is `contactsurveys_dir()`.

Value

Character vector of file paths under dir (absolute paths).

See Also

`delete_contactsurveys_files()` `delete_survey()` `delete_contactsurveys_dir()` `download_survey()`
`contactsurveys_dir()`

Examples

```
ls_contactsurveys()
```

```
print.csbib                    Print a csbib citation
```

Description

Print a csbib citation

Usage

```
## S3 method for class 'csbib'  
print(x, ...)
```

Arguments

x A "csbib" object.
... Additional arguments passed to methods.

Value

Invisibly returns x.

Index

contactsurveys_dir, 2
contactsurveys_dir(), 5, 7, 8

delete-files
 (delete_contactsurveys_files),
 3

delete_contactsurveys_dir
 (delete_contactsurveys_files),
 3

delete_contactsurveys_dir(), 4, 8
delete_contactsurveys_files, 3
delete_contactsurveys_files(), 4, 8
delete_survey, 4
delete_survey(), 8
download_survey, 4
download_survey(), 2, 4, 8

get_citation, 5

is_doi, 6

list_surveys, 7
list_surveys(), 2, 5
ls_contactsurveys, 7

print.csbib, 8

Renviron, 5

Sys.setenv(), 5

tempdir(), 2, 5, 7
tools::R_user_dir(), 2, 5

zen4R::get_citation(), 5